



SAFETY DATA SHEET INFORMATION

For further information: Please refer to the Safety Data Sheet following

Issue: October 18

PRODUCT: Bright Aluminium
Other Names: Oil Based Aluminium Roof Paint
Uses: Decorative and protective coating
Signal Word: Danger

UN No.:	1263
Dangerous Goods Class:	3
Subsidiary Risk:	None
Packing Group:	III
Hazchem Code:	3Y
Poisons Schedule:	S5

Hazardous Nature:	This product is classified as hazardous in accordance with GHS criteria in Australia
Hazard Statement:	Flammable liquid and vapour
GHS Classification:	Flammable Liquids: 3; Aspiration Toxicant: 1; Skin Corrosion/Irritation: 2; Chronic Aquatic Toxicant: 2

Physical Characteristics (Typical)		Section 9 of the SDS
Appearance	Silver metallic viscous liquid	
Boiling Point/Range (°C):	>150 C	
Flash Point (°C):	>35 C	
Specific Gravity/Density (g/ml @ 15°C):	Approx. 0.9	
pH:	Not established	
Chemical Stability:	Stable at room temperature and pressure	
Reactivity:	Excessive heat, oxidising agents, open flames and other sources of ignition	

Product Ingredients			Section 3 of the SDS
<u>Ingredient</u>	<u>CAS Number</u>	<u>Proportion</u>	
Naphtha, Petroleum, Hydrodesulfurized Heavy	64742-82-1	50-60%	
Hydrocarbon resin, postpolymerised with maleic anhydride	64742-16-1	20-30%	
Solvent Naphtha, Petroleum, Light Aromatic	64742-95-6	10-20%	

For further ingredients information, please refer to the full MSDS

GHS Pictograms

Section 2 of the SDS

Flame



Silhouette/star



Exclamation Mark



Dead fish/tree



DEFINITIONS

Dangerous Goods	Products that are regulated for transport under the UN International guidelines are classified as Dangerous Goods. Products can be classified by their physical characteristics and may have only one Dangerous Goods designation, although may have a subsidiary risk. These products may be Dangerous Goods for transport by Air and Sea, but may not be classed as Dangerous Goods by Road and Rail in Australia. Refer to the Australian Code for Transport of Dangerous Goods by Road and Rail (ADG) for more information.
Hazardous Substances	Hazardous Substances are those products that are intrinsically hazardous by virtue of their chemical nature, rather than as a condition of their misuse. These hazards include mutagens, teratogens, carcinogens, and products that are harmful or irritant in nature. These products may or may not carry a Dangerous Goods classification.
Poisons	Poisons are products that are regulated by the dose or exposure, often having physical and chemical effects at certain concentrations particular to the nature of the product. The associated warnings, cautions and First Aid instruction are prescriptive under the regulation in Australia.

1. IDENTIFICATION

Product Name: Bright Aluminium
Other Names: Oil Based Aluminium Roof Paint
Chemical Family: Not known
Molecular Formula: Not known
Recommended Use: Decorative and protective coating
Supplier: Duralex Paints Pty Ltd.
ABN: 17 000 392 227
Address: 3 – 5 Muriel Avenue, Rydalmere NSW 2116
Telephone: +61 2 9638 0568
Fax: +61 2 9684 1864
Emergency Phone: +61 2 9638 0568
All other inquiries: +61 2 9638 0568

2. HAZARDS IDENTIFICATION

Hazard Nature

Hazard Category

F: Flammable; T: Toxic; Xi: Irritant

GHS Classification

Flammable Liquids: 3; Aspiration Toxicant: 1; Skin Corrosion/Irritation: 2; Chronic Aquatic Toxicant: 2

GHS Pictograms

Flame

Silhouette/star

Exclamation Mark

Dead fish/tree



Hazard Statement

Flammable liquid and vapour

Hazard Statements

H226: Flammable liquid and vapour
H304: May be fatal if swallowed and enters airways
H315: Causes skin irritation
H336: May cause drowsiness or dizziness
H411: Toxic to aquatic life with long lasting effects

Precautionary Statements

P102: Keep out of reach of children.
P103: Read label before use.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P242: Use only non-sparking tools.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301+310: IF SWALLOWED: Immediately call a Doctor or Poisons information Centre on 131126
P331: Do NOT induce vomiting.
P403+233: Store in a well ventilated place. Keep container tightly closed.
P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501: Dispose of contents, or container in accordance with local/regional/national/international regulation.

Dangerous Goods Classification 3

Poisons Schedule S5

Signal Word Danger

3. COMPOSITION: Information on Ingredients

Chemical Ingredient	CAS Number	Proportion (% v/v)
Naphtha, Petroleum, Hydrodesulfurized Heavy	64742-82-1	50-60%
Hydrocarbon resin, postpolymerised with maleic anhydride	64742-16-1	20-30%
Solvent Naphtha, Petroleum, Light Aromatic	64742-95-6	10-20%
Aluminium Powder	7429-90-5	10-15%
Non hazardous ingredients	Various	Balance to 100%

4. FIRST AID MEASURES

For advice, contact Poisons Information Centre (Phone Australia: 13 1126) or a doctor.

Ingestion

If swallowed, DO NOT induce vomiting. Keep at rest. Seek immediate medical attention.

Eye Contact

Flush eyes with large amounts of water until irritation subsides. Seek immediate medical attention.

Skin Contact

Flush area with large amounts of water and wash area with soap if available. Remove contaminated clothing, including shoes, and launder before reuse. Seek medical attention for skin irritations.

Inhalation

Using proper respiratory protection, immediately remove the affective victim from exposure. Administer artificial respiration if breathing has stopped. Keep at rest. Seek immediate medical attention.

First Aid Facilities

Provide eye baths and safety showers.

Medical Attention

Treat according to symptoms.

5. FIRE FIGHTING MEASURES

Shut off product that may 'fuel' a fire if safe to do so. Allow trained personnel to attend a fire in progress providing fire fighters with this Safety Data Sheet. Prevent extinguishing media from escaping to drains and waterways.

Suitable Extinguishing Media

Alcohol resistant foam or if unavailable, dry chemical or foam.

Hazards from combustion products

This product is flammable and has the potential to develop explosive mixtures with air and extreme heat.

Precautions for fire fighters and special protective equipment

Full protective clothing and self contained breathing apparatus.

Hazchem Code

3Y

6. ACCIDENTAL RELEASE MEASURES**Emergency Procedures**

Prevent product from escaping to drains and waterways. Contain leaking packaging in a containment drum. Prevent vapours or dusts from building up in confined areas. Ensure that drain valves are closed at all times. Clean up and report spills immediately.

Methods and materials for containment***Major Land Spill***

- Eliminate sources of ignition.
- Warn occupants of downwind areas of possible fire and explosion hazard, where present.
- Prevent product from entering sewers, watercourses, or low-lying areas.
- Keep the public away from the area.
- Shut off the source of the spill if possible and safe to do so.
- Advise authorities if substance has entered a watercourse or sewer or has contaminated soil or vegetation.
- Take measures to minimise the effect on the ground water.
- Contain the spilled product using the resources in the spill kit.
- Recover by pumping – use explosion proof pump or hand pump – or with a suitable absorbent material.
- Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.
- See "First Aid Measures" and "Stability and Reactivity"

Major Water Spill

- Eliminate any sources of ignition.
- Warn occupants and shipping in downwind areas of possible fire and explosion hazard, where present.
- Notify the port or relevant authority and keep the public away from the area.
- Shut off the source of the spill if possible and safe to do so.
- Confine the spill if possible.
- Remove the product from the surface by skimming or with suitable absorbent material.
- Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.
- See "First Aid Measures" and "Stability and Reactivity".

7. HANDLING AND STORAGE

Precautions for Safe Handling

This product is flammable. Do not open near open flame, sources of heat or ignition. No smoking. Keep container closed. Handle containers with care. Open slowly to control possible pressure release. Use grounding leads to avoid discharge (electrical spark).

Conditions for Safe Storage

Store in a cool, dry place away from direct sunlight. Do not pressurise, cut, heat or weld containers - residual vapours are flammable. This product is flammable and will fuel a fire in progress.

Incompatible Materials

None established

8. EXPOSURE CONTROLS: PERSONAL PROTECTION

National Exposure Standards

The time weighted average concentration (TWA) for this product is: None established: Consider 5gm/m³, which means the highest allowable exposure concentration in an eight-hour day for a five-day working week. The short term exposure limit (STEL) is: Not known, which is the maximum allowable exposure concentration at any time. Replacing a TWA or STEL value for some products is a Peak Limitation value (Peak): Not established applies in this case. In addition to the exposure concentrations may be a subsidiary caution in such cases where the product is a skin sensitizer, represented as (Sen), where None applies in this case.

Biological Limit Values (BLV)

None established

Engineering Controls: Ventilation

The use of local exhaust ventilation is recommended to control process emissions near the source. Laboratory samples should be handled in a fume hood. Provide mechanical ventilation of confined spaces. Use explosion proof equipment.

Personal Protective Equipment

Respiratory Protection: Where concentrations in air may approach or exceed the limits described in the National Exposure Standards, it is recommended to use a half-face filter mask to protect from overexposure by inhalation. A type 'A' filter material is considered suitable for this product.

Eye Protection: Always use safety glasses or a face shield when handling this product.

Skin/Body Protection: Always wear long sleeves, long trousers, or coveralls, and enclosed footwear or safety boots when handling this product. It is recommended that chemical resistant gloves be worn when handling this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Property	Unit of measurement	Typical Value
Appearance	None	Silver metallic viscous liquid
Boiling Point/Range	°C	>150° C
Flash Point	°C	>35° C
SG/Density (@ 15°C)	g/ml; kgm ⁻³	Approx. 0.9
Vapour Pressure @ 20°C	kPa	Not known
Vapour Density @ 20°C	g/ml; kgm ⁻³	Not known
Autoignition Temperature	°C	Not established
Explosive Limits in Air	% vol/vol	Not known
Viscosity @ 20°C	cPs, mPas	Not known
Percent volatiles	% vol/vol	Hydrocarbons
Acidity/alkalinity as pH	None	Not established

Property	Unit of measurement	Typical Value
Solubility in Water	g/l	None
Other solvents	-	Hydrocarbons

The values listed are indicative of this product's physical and chemical properties. For a full product specification, please consult the Technical Data Sheet.

10. STABILITY AND REACTIVITY

Chemical stability

Stable at room temperature and pressure

Conditions to avoid

Excessive heat, oxidising agents, open flames and other sources of ignition

Hazardous decomposition products

Carbon dioxide, carbon monoxide on decomposition or incomplete oxidation

Hazardous reactions

Strong oxidising agents, excessive heat

Hazardous polymerisation

Will not occur

11. TOXICOLOGICAL INFORMATION

Acute Effects

Ingestion

Swallowing will result in nausea, headache, central nervous system effects. Product can be aspirated to the lungs on vomiting resulting in chemical pneumonitis and long term lung damage. Small amounts of this product will cause irritation and a burning sensation in the throat, trachea, and oesophagus.

Eye Contact

Eye contact with this product will cause redness and swelling with a burning sensation and blurred vision. Prolonged eye damage is possible with this product.

Skin Contact

This product will result in defatting of the skin with prolonged or repeated contact. Drying and cracking of skin risks the possible absorption of other chemical products potentially in use.

Inhalation

Vapours at elevated temperatures will cause dizziness and drowsiness. Vapours at room temperature should be controlled through adequate (do not use in confined spaces) or mechanical ventilation.

Chronic Effects

Repeated or prolonged contact with this product will result in irritant contact dermatitis if PPE precautions are not observed.

Other Health Effects Information

Persons with pre-existing skin conditions will be sensitive to this product.

Toxicological Information

Oral LD₅₀: Xylene: (rat) > 2000 mg/kg

Dermal LD₅₀: Xylene: (rabbit) > 2000 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

Aquatic Toxicity:

Fish Toxicity LC₅₀: This product is considered harmful to aquatic environments.
 Daphnia Magna EC₅₀: This product is considered harmful to aquatic environments.
 Blue-green algae: This product is considered harmful to aquatic plant life.
 Green algae: This product is considered harmful to aquatic plant life.

Persistence/Biodegradability: Elements of this product are expected to persist.

Mobility: This product is likely to be mobile on release to the environment.

13. DISPOSAL CONSIDERATIONS

Disposal Methods

Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor. Care should be taken to ensure compliance with national and local authorities. Packaging may still contain product residue that may be harmful. Ensure that empty packaging is managed in accordance with Dangerous Goods regulations.

Special Precautions

This product is not suitable for disposal by either landfill or via municipal sewers, drains, natural streams or rivers. This product should be treated and disposed through chemical waste treatment, or considered for use in recycling.

14. TRANSPORT INFORMATION

Road and Rail Transport		Marine Transport		Air Transport	
UN No.	1263	UN No.	1263	UN No.	1263
Proper Shipping Name	Paint	Proper Shipping Name	Paint	Proper Shipping Name	Paint
DG Class	3	DG Class	3	DG Class	3
Sub. Risk	None	Sub. Risk	None	Sub. Risk	None
Packing Group	III	Packing Group	III	Packing Group	III
Hazchem	3Y	Hazchem	3Y	Hazchem	3Y

Dangerous Goods Segregation

This product is regulated as Class 3 Dangerous Goods, packing group III.

15. REGULATORY INFORMATION

Country/Region: Australia

Inventory: AICS

Status: Listed

Poisons Schedule: S5

16. OTHER INFORMATION

Reasons for Issue: New product; amalgamated supplier and regulatory updates in all sections

Abbreviations:

AICS: Australian Inventory of Chemical Substances

CAS Number: Chemical Abstracts Number

GHS: Global Harmonised System

IARC: International Agency for Research on Cancer

PPE: Personal Protective Equipment

N/R: Non-regulated

N/A: Not applicable

UN: United Nations

References:

- Supplier Safety Data Sheets
- <http://hsis.safework.gov.au/SearchHS.aspx> (October 18)
- Animal toxicology data: <http://chem.sis.nlm.nih.gov/chemidplus> (October 18)
- Ecotoxicology data: http://cfpub.epa.gov/ecotox/quick_query.htm (October 18)
- *Sax's Dangerous Properties of Industrial Materials*, Richard J Lewis Snr., pub. Canada (2005)

The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the writer's knowledge. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. This document should be taken as a safety guide for the product and its recommended uses, but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product. For further information, please contact Durablex Paints Pty Ltd.
