



DURALEX

PRODUCT INFORMATION SHEET

metalPRIME™

DESCRIPTION

Durablex metalPRIME™ is a water-based anti-corrosive primer offering excellent long term resistance to rust and corrosion for mild to medium, light industrial environments. With outstanding adhesion to both ferrous and non-ferrous substrates **Durablex metalPRIME™** can be top coated with a choice of 1 pack or 2 pack, waterbased or solvent containing products such as polyurethane or epoxy paints.

USES

Designed primarily for the protection of exterior steel, it is also suitable for stainless and galvanised steel, zincalume and aluminium. Ideal for interior structures and surfaces.

SURFACE PREPARATION

For new, bright unpainted metal, degrease, clean and dry to remove dust, oil, grease or other contaminants.

For previously painted surfaces or those with rust, white corrosion or mill scale, remove all loose matter with hand or power tools and remove dust, oil and grease. Spot prime as necessary.

APPLICATION

Apply 2 coats of **Durablex metalPRIME™** on prepared surfaces. Application by brush, roller or airless spray to dry film build 80-100 micron per coat on steel and 50-70 micron per coat on galvanised steel and non-ferrous metals. Surface temperature must be above 10°C during application and drying time. Touch dry in 30 minutes and able to be recoated after 2 hours.

VENTILATION

Allow adequate cross ventilation when painting indoors during and after use to dissipate water vapour.

Note: Mechanical ventilation is required if painting in an area with no natural ventilation.

CLEAN UP

Do not pour leftover paint down the drain. Wash all equipment with clean water. Any dried spots may be removed using methylated spirits and a clean cloth.

Note: Never allow waste water to enter storm water drains or sewers.

COVERAGE

Up to 11-13 square metres per Litre per coat.

SIZES

20, 10, 4, 1 Litre, 500 and 250mL.

RECYCLE

This can is recyclable. Check with your local council to see if it is participating in a steel can recycling programme.

ENVIRONMENT

Low odour. Low V.O.C. Environmentally friendly.

IMPORTANT

Keep out of reach of children. If contact with the eyes occurs, rinse with running water and seek help if irritation persists. If swallowed, do not induce vomiting. Give a glass of water and seek medical assistance or contact the Poison Information Centre (13 11 26).



The information given herein is believed to be accurate and reliable but is presented without guarantee, warranty or responsibility of any kind. Users of our products should perform their own tests to determine the suitability of each Durablex product for their particular purposes. This information is being constantly updated and subject to change without notice.

DURALEX
ENVIRONMENTALLY
AWARE

3-5 Muriel Avenue, Rydalmere N.S.W. 2116
PHONE: (02) 9638 0568 FAX: (02) 9684 1864

www.durablexpaints.com.au

NEVER POUR LEFTOVER PAINTS DOWN THE DRAIN

CLEANING UP AFTER PAINTING

(Industry standard for Water-based paint)

EXCESS/UNWANTED PAINT

- At the completion of a painting job, pour, brush or roll excess unwanted paint onto an absorbent material such as kitty litter, old rags, newspaper, cardboard, etc.
- Allow paint to dry, this could take up one week, then dispose with household waste collection services.

WASHING OF EQUIPMENT: (Two-Container Method)

- **20 Litre containers are best!**
- Wash brushes, rollers and other equipment in the **FIRST** container of water.
- Transfer the washed equipment to the **SECOND** container filled with clean water for a final rinse.
- Allow the containers to stand, overnight the paint solids will settle to the bottom, this usually takes about 12 hours. The clear water from the **FIRST** container may now be poured on the garden where it will be absorbed into the ground. Avoid areas near drains, streams, rivers or lakes.

DISPOSAL OF RESIDUE:

- Paint solids at the bottom of the first container can be scraped onto an absorbent material as previously described. Allow to dry, then dispose as previously described.
- The **SECOND** container can now be used as the first wash. Follow this cleaning system until the job is completed.

CAUTION:

- Never allow waste water to enter household storm water drains or sewers.

DISPOSAL OF LEFTOVER PAINT CONTAINERS

EMPTY OUT CONTAINER

Ensure paint container is as clean as possible.

RECYCLE STEEL CONTAINER

- The cleaned paint container can be disposed of via local steel recycling programs (check with your local Council).